



HARNESSES & LANYARDS

FIRST

THE NEW FIRST™ RANGE OF CE CERTIFIED FALL ARREST HARNESSES AND SHOCK ABSORBING LANYARDS FROM CAPITAL SAFETY



TOTAL COMPLIANCE, ABSOLUTE CONFIDENCE



TRUSTED FALL PROTECTION

HARNESSES & LANYARDS

HARNESSES

1 POINT FIRST™ HARNESS



1310102	UNI	PT	PT	0.95
1310103	S	PT	PT	0.95
1310101	XL	PT	PT	0.95

EN361

1 POINT FIRST™ HARNESS WITH BELT



1310108	UNI	PT	PT	PT	1.25
1310109	S	PT	PT	PT	1.25
1310107	XL	PT	PT	PT	1.25

EN361, EN358

2 POINT FIRST™ HARNESS



1310105	UNI	PT	PT	1.05
1310106	S	PT	PT	1.05
1310104	XL	PT	PT	1.05

EN361

2 POINT FIRST™ HARNESS WITH BELT



1310111	UNI	PT	PT	PT	1.25
1310112	S	PT	PT	PT	1.25
1310110	XL	PT	PT	PT	1.25

EN361, EN358

KITS

1 POINT FIRST™ HARNESS & TWIN LEG FIRST™ LANYARD



1329988	UNI
1329989	S
1329987	XL

1 POINT FIRST™ HARNESS & SINGLE LEG FIRST™ LANYARD



1329991	UNI
1329992	S
1329990	XL

LANYARDS



SINGLE LEG FIRST™ LANYARD (1310307)

2m, AJ501 & AJ595, 1.0kg

EN355



TWIN LEG FIRST™ LANYARD (1310308)

2m, AJ501 & AJ595, 1.5kg

SPECIFICATIONS

HARNESSES:

Webbing: 45mm Polyester
Stitching: High strength Polyester thread
Buckles: Zinc plated steel
D Rings: Zinc plated steel

LANYARDS:

Maximum arresting force: <6kN
Webbing: 45mm polyester
Stitching: High strength Polyester thread
Body Connector: AJ501 Steel Screw Carabineer, 21mm Gate, 25kN breaking strength
Anchor Connector: AJ595 Steel Scaffold hook, 50mm gate, 23kN breaking strength