

DBI-SALA® NANO-LOK™
FOR HOT WORK USE



THE FIRST EVER SELF RETRACTING LIFELINE DESIGNED FOR WELDING, GRINDING AND HIGH HEAT APPLICATIONS



DURABLE

Reinforced webbing with Nomex®/Kevlar® fiber to withstand sparks, weld splatter and other high heat exposure.

VERSATILE

5 different Nano-Lok® configurations, single and twin-leg, that can be connected at foot level to meet your specific needs.

SAFE

Arc flashed to 8 calories (8cal/cm²), for hot work use in applications like welding, grinding and torching. Meets or exceeds industry standards. CE EN360:2002.



FOR HOT
WORK USE



THE ULTIMATE IN FALL PROTECTION

NANO-LOK™ FOR HOT WORK USE FEATURES



REF: 3101521

Single-Leg
Steel Snap Rebar hook
63 mm opening
1.6 kg – 2 m



REF: 3101522

Single-Leg
Alum. Snap Rebar hook
57 mm opening
1.5 kg – 2 m



REF: 3101523

Single-Leg
Steel Snap hook
19 mm opening
1.6 kg – 2 m



REF: 3101524

Twin-Leg
Steel Snap Rebar hook
63 mm opening
3.1 kg – 2 m



REF: 3101525

Twin-Leg
Alum. Snap Rebar hook
57 mm opening
3.2 kg – 2 m

SPECIFICATIONS:

Reinforced webbing with Nomex® / Kevlar® fiber*. Resist to sparks and weld splatters. Arc-flashed resistant to 8 cal / cm²
 Certification: CE EN360 : 2002
 Capacity: 140 kg
 Connection level: Can be connected at foot level
 Length = 2 m

*DuPont™, Kevlar®, and Nomex® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.



CAPITAL SAFETY - EMEA

Le broc Center, Z.I. 1re Avenue – BP15
06511 Carros Le Broc Cedex, FRANCE
t: +33 (0) 4 97 10 00 10 f: +33 (0) 4 93 08 79 70

5a Merse Road, North Moons Moat
Redditch, B98 9HL, UK
t: +44 (0) 1527 548 000 f: +44 (0) 1527 591 000

00 800 999 55500

information@capitalsafety.com

capitalsafety.com