



PRODUCT CODE: RE-PROMA-KN95

PRODUCT DESCRIPTION: FOLD-FLAT AIRMAXX KN95 FFP2 DUST MASK

MATERIALS

NOSECLIP	Aluminium strip, glue bonded
MASK/RESPIRATOR	4 layers – top and bottom are non-woven poly-propylene fabric, middle layer is meltblown poly-propylene fabric, as well as a spongy non-woven filament, ultrasonic welding of layers.
HEAD STRAPS	Spandex elastic tape, glue bonded to mask

COMPLIANCY

EN 149



CERTIFICATION

EN/ISO REQUIREMENT	EN 149:2001	GB 2626:2006
PROTECTION RATING	FFP2	KN95
CE REQUIREMENT	CE 0194	N/A

SPECIAL FEATURES

- Fold-flat dust mask with adjustable noseclip to ensure a better fit (especially with glasses and goggles) and minimum ingress of dust particles.
- Protects against materials in concentrations up to 12x OEL (Occupational Exposure Limit) or 4x APF (Assigned Protection Factor).
- Pre-stretched, latex-free head straps.
- Protects against moderate levels of dust, as well as solid and liquid aerosols.

WARNINGS

This product will not protect against fumes, gases or vapours. It is only for dust, droplets and bacteria when used under the correct safety protocols.

This product does not supply oxygen. Ensure that you use it in well ventilated areas containing sufficient oxygen.

This is a single use respirator. Discard it after a single shift, or after 8 hours of use.

Leave work area immediately if breathing becomes difficult, or dizziness occurs.

OTHER INFORMATION

SIZING	1 sealed packet of 10 individual masks in a packet
PACKAGING	100 packets per carton (1000pcs per carton)
STORAGE	Respirators must be placed in a sealed packet or container, and stored in an environment free of dust, chemicals, moisture, excessive heat and direct sunlight. Failure to do so may affect the performance and shelf life of these products.

SUGGESTED ENVIRONMENTS

FFP2 Dust Masks are ideal for medium level dust environments i.e. plastering and sanding.