





PRODUCT CODE: RE-DISDU-FFP1

PRODUCT DESCRIPTION: AIRMAXX DISPOSABLE FFP1 DUST MASK

MATERIALS				
NOSECLIP	Aluminium strip, glue	Aluminium strip, glue bonded		
MASK/RESPIRATOR	3 layers – top and bottom are non-woven 100% polyester, middle layer is meltblown nonwoven polyester			
HEAD STRAPS	Spandex elastic tape, glue bonded to mask			
COMPLIANCY	CERTIFICATION		SPECIAL FEATURES	
EN 149	EN/ISO REQUIREMENT	EN 149:2001	<ul> <li>Low profile dust mask with adjustable noseclip to ensure a better fit (especially with glasses and goggles) and minimum ingress of dust particles.</li> <li>Protects against materials in concentrations up to 4x OEL (Occupational Exposure Limit) or 4x APF (Assigned Protection Factor).</li> <li>Pre-stretched, latex-free head straps.</li> <li>Protects against low levels of dust, as well as solid and liquid aerosols.</li> </ul>	
	PROTECTION RATING	FFP1 NR		
	CE REQUIREMENT	CE 0194		
	SABS	SANS 50149:2003		
	NRCS	NRCS/8072/0162		

## WARNINGS

This product will not protect against fumes, gases or vapours.

This product does not supply oxygen. Ensure that you use it in well ventilated areas containing sufficient oxygen.

This is a single use respirator. Discard it after a single shift, or after 8 hours of use.

Leave work area immediately if breathing becomes difficult, or dizziness occurs.

Consult your Safety Officer or an approved sales rep when implementing a respiratory protection programme.

OTHER INFORMATION		
SIZING	1 sealed packet of 20 individual masks in a box	
PACKAGING	20 boxes per carton	
STORAGE	Respirators must be placed in a sealed packet or container, and stored in an environment free of dust, chemicals, moisture, excessive heat and direct sunlight. Failure to do so may affect the performance and shelf life of these products.	

## SUGGESTED ENVIRONMENTS

FFP1 Dust Masks are ideal for low level dust environments i.e. hand sanding, drilling and cutting.

