



**PRODUCT CODE:** HS-HZNLLN-20M    **PRODUCT DESCRIPTION:** 20 Metre Temporary Horizontal Lifeline

## PRODUCT COMPLIANCE

<b>CERTIFICATION</b>	EN795 Class C – Flexible anchor points EN795 Class B – Anchor sling EN362 – Connector
<b>PACKAGING</b>	Individually packed in a box and serial numbered with user instruction leaflet.

## MATERIALS

<b>WEBBING</b>	<ul style="list-style-type: none"> <li>• 30mm wide polyester webbing (lifeline)</li> <li>• 44mm wide polyester webbing (anchor point)</li> </ul>
<b>D-RINGS</b>	<ul style="list-style-type: none"> <li>• 50mm wide D-Ring (anchor point)</li> </ul>
<b>RATCHET</b>	Corrosion-resistant steel ratchet

## TECHNICAL FEATURES

<b>LIFELINE WEBBING</b>	20m bright yellow webbing with a loop on each end to connect with to a carabiner.
<b>ANCHOR STRAP (2)</b>	Versatile straps used to setup lifeline between 2 anchor points .
<b>CARABINER (2)</b>	Screw gate carabiner with automatic closing function which connects the Temporary Lifeline to an anchor point.
<b>CARRY BAG</b>	Designed to store all components of this system and protect it from possible damage.
<b>RATCHET SYSTEM</b>	The simple ratchet system is easy to use whilst effective at creating a tensioned lifeline.

## SUGGESTED ENVIRONMENTS

This product has been designed to be used in a covered environment which is not exposed to the outdoor elements for extended periods of time.

## WARNINGS

MAXIMUM WEIGHT	Certified to a maximum of 2 x 140kg users – 280kg.
CONNECTIONS	This device must be securely set up between certified anchor points as well as connected by a certified connector.
POSITIONING	This device must be setup as high as possible to reduce the fall clearance as well as trip hazard.
PRODUCT LIFESPAN	The components have a maximum lifespan of 5 years.
IN THE EVENT OF A FALL	Should this product have been subject to a fall, or there is visible damage, it should be removed from service immediately and not used until it has been inspected by a REBEL Subject Matter Expert.
INTERMEDIATES	Should this product span a length of more than 5 metres there must be an intermediate included in the system to reduce the forces in the event of a fall as well as fall clearance.
EXPOSURE	This product is designed for temporary use – It should not be left setup for periods longer than 5 days at any given time.
COMPLY TO INSTRUCTION MANUAL	The user must comply to the user instruction manual. Not adhering could lead to serious injury or death.