

3M DBI-SALA EXOFIT XE200 HARNESS

Comfort Positioning/Rescue Safety Harness with auto-locking quick connect buckles

 PRODUCT CODE: CAPIHE-1112735-01
 SIZE 1

 PRODUCT CODE: CAPIHE-1112736-02
 SIZE 2

 PRODUCT CODE: CAPIHE-1112737-03
 SIZE 3

PRODUCT FEATURES		
NANO-LOK ADAPTER UNDER D-RING:	Simple Nano-Lok connection	
REAR FALL ARREST ATTACHMENT POINT:	• Large stand-up D-ring – Aluminium - blue anodisation	
FRONT FALL ARREST ATTACHMENT POINT:	Standard D-ringAluminium - blue anodisation	
RESCUE ATTACHMENT POINT:	• Rescue textile loop – Textile with wear resistant tube web	
WORK POSITIONING ATTACHMENT POINTS:	Large cranked D-ringAluminium - blue anodisation	
LEG BUCKLES:	 Auto-locking quick connect Steel - zinc plated/black paint, aluminium - grey anodisation 	
CHEST BUCKLES:	 Quick connect Steel - zinc plated/black paint, aluminium - grey anodisation 	
WAIST BUCKLES:	 Auto-locking quick connect Steel - zinc plated/black paint, aluminium - grey anodisation 	
ADJUSTMENT:	Legs, waist, torsoTorso: Revolving adjusterSteel/aluminium - ratchet buckle	
WEBBING:	45mm Polyester	
THREAD:	Polyester	
ADDITIONAL FEATURES:	 Front & rear fall indicators Leg, shoulder & waist padding 2x Auto-resetting/repositionable lanyard keepers RFID Equipped Suspension trauma straps Lifeline attachment point 	
WEIGHT CAPACITY:	140kg	
STANDARDS:	CE EN361:2002; EN358:2019; EN1497:2007UKCA	





PRODUCT SPECIFICATIONS

3M DBI-SALA EXOFIT XE200 HARNESS

Comfort Positioning/Rescue Safety Harness with auto-locking quick connect buckles



WEIGHT

	≺····>	k g €
CAPIHE-1112735-01	SIZE 1	2.90
CAPIHE-1112736-02	SIZE 2	2 . 95
CAPIHE-1112737-03	SIZE 3	3.00

IMPORTANT NOTICE

The mounting and use of the product described within this document assumes that the user has previous experience of this type of product and that it will be assembled by a competent professional according to product documentation. Before any use of this product it is recommended to complete some trials to validate the performance of the product within its expected application.

All information and specification details contained within this document are inherent to this specific 3m product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user.

Compliance to the information and specification relative to the product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M group (who cannot verify or control these elements) would not be held responsible for the consequences of any violation of these rules which remain external to its decision and control.

Warranty conditions for products are determined with the sales contract documents and with the mandatory and applicable law, excluding any other warranty or compensation.









